



LAE SPOED TIP WA - LOW SPEED TIP TRAILER TSW3T, TSW5T



BESKRYWING

- Stewige lae spoed wa vir trekker gebruik

SPESIFIKASIES

Model	TSW3T	TSW5T
Laai Kapasiteit	3 Ton	5 Ton
Bande	900 x 16"	900 x 16"
Mates	2,3 x 3,6 m	2,3 x 3,6 m
Sy Hoogte	400 mm	400 mm
Parkeerrem	Meganies	Meganies
Diensrem	Inlooprem	Inlooprem
Silinder	4 fase teleskopies	4 fase teleskopies

Optoneel

Vuilgoed / Kuilvoer hok

Hoogte van hok	1,2 m
Hok materiaal	Plaatgaas
Agter hokklap	Verwyderbare agterklap (swaai tipe)

DESCRIPTION

- Ruggedly built low speed trailers for use by tractor

SPECIFICATIONS

Serial	TSW3T	TSW5T
Load Capacity	3 Ton	5 Ton
Tires	900 x 16"	900 x 16"
Measurements	2,3 x 3,6 m	2,3 x 3,6 m
Height of Sides	400 mm	400 mm
Parking Brake	Mechanical	Mechanical
Service Brake	Run in service brake	Run in service brake
Cylinder	4 phase telescopic	4 phase telescopic

Optional

Refuse / Silage cage

Height of cage	1,2 m
Cage material	Expanded metal
Tailgate	Removable tail gate to fit cage (swing type)

BPI Manufacturing
Reg: 2011/139199/07
Vat: 4480222431
Import/Export no: 20143323

Tel: +27 (0)56 515 1066/7 | Fax: +27 (0)56 515 4754 | Email: rocco@bpimplemente.co.za
First Avenue, Bothaville, Freestate, South Africa | PO Box 80, Bothaville, 9660, RSA
www.bpimplemente.co.za
Director: C.J. Botha

CUSTOM SOLUTIONS SINCE 1968